



# Intimidator UTV Fluid Quick Reference

This chart describes the lubricants and fluids utilized in Intimidator off-road vehicles. All of the fluids indicated in the chart are used to fill the units at the factory and are also the fluids that Intimidator recommends for future fluid changes.

Model	Item	Fluid	Volume
<b>Kohler 750cc</b>	Brake Fluid	DOT 3	Fill to level between Min and Max marks
	Front Differential Oil	Shell Spirax S3 TLV	180 ml (6.09 oz.)
	Rear Differential Oil	Shell Spirax S4 AX 80W-90	550 ml (18.60 oz.)
	Transmission/Gearbox Oil	Pennzoil Plat LV MVATF	700 ml (23.67 oz.)
	Engine Oil	Intimidator SYN 5W-40	2 qt.
<b>Intimidator 800cc</b>	Brake Fluid	DOT 3	Fill to level between Min and Max marks
	Front Differential Oil	Shell Spirax S3 TLV	180 ml (6.09 oz.)
	Rear Differential Oil	Shell Spirax S4 AX 75W-140	550 ml (18.60 oz.)
	Transmission/Gearbox Oil	Pennzoil Plat LV MVATF 75W-140	420 ml (14.20 oz.)
	Engine Oil	Intimidator SYN 5W-40	2 qt.
<b>Kohler 1000cc Diesel</b>	Brake Fluid	DOT 3	Fill to level between Min and Max marks
	Front Differential Oil	Shell Spirax S3 TLV	180 ml (6.09 oz.)
	Rear Differential Oil	Shell Spirax S4 AX 80W-90	550 ml (18.60 oz.)
	Transmission/Gearbox Oil	Pennzoil Plat LV MVATF	700 ml (23.67 oz.)
	Engine Oil	Intimidator SYN 5W-40	2.5 qt.
<b>Intimidator GC1K</b>	Brake Fluid	DOT 3	Fill to level between Min and Max marks
	Front Differential Oil	Shell Spirax S3 TLV	180 ml (6.09 oz.)
	Rear Differential Oil	Shell Spirax S4 AX 80W-90	550 ml (18.60 oz.)
	Transmission/Gearbox Oil	Valvoline SYN 75W-140	750 ml (25.36 oz.)
	Engine Oil	Intimidator SYN 5W-40	2 qt.
<b>Intimidator Electric Vehicle</b>	Brake Fluid	DOT 3	Fill to level between Min and Max marks
	Front Differential Oil	Hydraulic Fluid	180 ml (6.09 oz.)
	Rear Differential Oil	John Deere 303	550 ml (18.60 oz.)
	Transmission/Gearbox Oil	Pennzoil Plat LV MVATF	700 ml (23.67 oz.)
	Battery Water	Distilled Water	At least ¼" above the plates, no more than ½" below the filler neck